

ignition system designed and maintained to reduce the release of electrical energy.

[64 FR 72775, Dec. 28, 1999, as amended at 65 FR 219, Jan. 4, 2000]

**§ 250.115 How do I determine well producibility?**

You must follow the procedures in this section to determine well producibility if your well is not in the GOM. If your well is in the GOM you must follow the procedures in either this section or in § 250.116 of this subpart.

(a) You must write to the Regional Supervisor asking for permission to determine producibility.

(b) You must either:

(1) Allow the District Supervisor to witness each test that you conduct under this section; or

(2) Receive the District Supervisor's prior approval so that you can submit either test data with your affidavit or third party test data.

(c) If the well is an oil well, you must conduct a production test that lasts at least 2 hours after flow stabilizes.

(d) If the well is a gas well, you must conduct a deliverability test that lasts at least 2 hours after flow stabilizes, or a four-point back pressure test.

**§ 250.116 How do I determine producibility if my well is in the Gulf of Mexico?**

If your well is in the GOM, you must follow either the procedures in § 250.115 of this subpart or the procedures in this section to determine producibility.

(a) You must write to the Regional Supervisor asking for permission to determine producibility.

(b) You must provide or make available to the Regional Supervisor, as requested, the following log, core, analyses, and test criteria that MMS will consider collectively:

(1) A log showing sufficient porosity in the producible section.

(2) Sidewall cores and core analyses that show that the section is capable of producing oil or gas.

(3) Wireline formation test and/or mud-logging analyses that show that the section is capable of producing oil or gas.

(4) A resistivity or induction electric log of the well showing a minimum of 15 feet (true vertical thickness except for horizontal wells) of producible sand in one section.

(c) No section that you count as producible under paragraph (b)(4) of this section may include any interval that appears to be water saturated.

(d) Each section you count as producible under paragraph (b)(4) of this section must exhibit:

(1) A minimum true resistivity ratio of the producible section to the nearest clean or water-bearing sand of at least 5:1; and

(2) One of the following:

(i) Electrical spontaneous potential exceeding 20-negative millivolts beyond the shale baseline; or

(ii) Gamma ray log deflection of at least 70 percent of the maximum gamma ray deflection in the nearest clean water-bearing sand—if mud conditions prevent a 20-negative millivolt reading beyond the shale baseline.

**§ 250.117 How does a determination of well producibility affect royalty status?**

A determination of well producibility invokes minimum royalty status on the lease as provided in 30 CFR 202.53.

**§ 250.118 Will MMS approve gas injection?**

The Regional Supervisor may authorize you to inject gas on the OCS, on and off-lease, to promote conservation of natural resources and to prevent waste.

(a) To receive MMS approval for injection, you must:

(1) Show that the injection will not result in undue interference with operations under existing leases; and

(2) Submit a written application to the Regional Supervisor for injection of gas.

(b) The Regional Supervisor will approve gas injection applications that:

(1) Enhance recovery;

(2) Prevent flaring of casinghead gas;

or

(3) Implement other conservation measures approved by the Regional Supervisor.